

# Floating Joint 25A-J□ Series

RoHS

## How to Order



### Stainless steel type

25A - J S 32 - 10-125 □

Series compatible with secondary batteries

Stainless steel type

Applicable bore size [mm]

Symbol	Applicable bore size [mm]
10	10
16	10, 16
20	20
32	25, 32
40	40
63	50, 63

Thread nominal size

Nominal thread size	Applicable cylinder nominal thread size
4-070	M4 x 0.7
5-080	M5 x 0.8
8-125	M8 x 1.25
10-125	M10 x 1.25
14-150	M14 x 1.5
18-150	M18 x 1.5

Material of dust cover

Symbol	Material
Nil	Fluororubber (FKM)
S	Silicone rubber (Si)

\* The 25A- series specifications and dimensions are the same as those of the standard model.

For details, refer to the **Web Catalog**.

## How to Order

### Standard type

25A - JA 80 - 22-150

Series compatible with secondary batteries

Applicable bore size [mm]

Model	Symbol	Applicable bore size [mm]
Standard	80	80
	100	100

\* For ø63 or less, please consider using the stainless steel type 25A-JS series.

Thread nominal size (Standard)

Nominal thread size	Applicable cylinder nominal thread size
22-150	M22 x 1.5
26-150	M26 x 1.5

\* The 25A- series specifications and dimensions are the same as those of the standard model.

For details, refer to the **Web Catalog**.



## How to Order

### For compact cylinders

25A - J B 40 - 8-125

Series compatible with secondary batteries

For compact cylinders/Female thread

Applicable bore size [mm]

Symbol	Applicable bore size [mm]
12	12
16	16
20	20
25	25
40	32, 40
63	50, 63
80	80
100	100

Thread nominal size

Nominal thread size	Applicable cylinder nominal thread size
3-050	M3 x 0.5
4-070	M4 x 0.7
5-080	M5 x 0.8
6-100	M6 x 1
8-125	M8 x 1.25
10-150	M10 x 1.5
16-200	M16 x 2
20-250	M20 x 2.5

\* The 25A- series specifications and dimensions are the same as those of the standard model.

For details, refer to the **Web Catalog**.

