

# Made to Order Common Specifications: -XC65: Made of Stainless Steel (Combination of XC7 and XC68)



## 48 Made of Stainless Steel (Combination of XC7 and XC68)

Symbol  
-XC65

Suitable for the cases it is likely to generate rust by being immersed in the water and corrosion.

### Applicable Series

Series	Description	Model	Action	Note	Vol. no. (for std model)
MB	Air cylinder	MB-Z	Double acting, Single rod	Except ø125	②-1 From P. 392
		MBW-Z	Double acting, Double rod	Except ø125 and air cushion	
MB1	Smooth cylinder	MBY-Z	Double acting, Single rod		②-3 From P. 183
		MB1-Z	Double acting, Single rod	Except ø125	②-1 From P. 440
CA2	Air cylinder	MB1W-Z	Double acting, Double rod	Except ø125	
		Smooth cylinder	CA2Y-Z	Double acting, Single rod	

### Specifications

Parts changed to stainless steel	Tie-rod, Tie-rod nut, Cushion valve, Piston rod (with hard chrome plated), Rod end nut
Maximum manufacturable stroke (mm)	Double acting, Single rod: 1600 Double acting single rod with rod boot: 1000
Specifications other than above and external dimensions	Same as standard type

### How to Order

Standard model no.            - XC65  
↓  
 Made of stainless steel  
 (Combination of XC7 and XC68)